

Fixation clips

Edge clips



Technical specifications

Plastic clip / Cable tie : Polyamide 6.6 HS, black, impact resistant, heat resistant, UV resistant
 Metal clamp : Spring steel, hardened coated surface to ensure protection against corrosion
 Temperature range : -40 °C up to +120 °C (short time 140 °C)

Scan this QR code for article numbers, current prices and stock information and to order directly.

Fixation clip type	Profile thickness (in mm)	Position of cable in relation to profile	Cable tie orientation	PU (pcs.)
KC1 *	0.7 - 3.0	Top	Perpendicular on the profile	100/500
KC2 *	0.7 - 3.0	Side	Perpendicular on the profile	100/500
KC3 *	0.7 - 3.0	Top	Parallel direction of the profile	100/500
KC5 *	0.7 - 3.0	Side	Parallel direction of the profile	100/500
KC15 *	0.7 - 3.0	Top and side	Four directions	100/500
KC17 **	0.7 - 3.0	Top	Perpendicular on the profile	100/500
KC18 **	0.7 - 3.0	Side	Perpendicular on the profile	100/500
KC19 **	0.7 - 3.0	Top	Parallel direction of the profile	100/500
KC20 **	0.7 - 3.0	Side	Parallel direction of the profile	100/500
KC126 *	0.7 - 3.0	Side	Four directions	100/500
KC107 *	3.0 - 6.0	Top and side	Four directions	100/500
KC87 *	3.0 - 6.0	Top	Parallel direction of the profile	100/500
KC88 *	3.0 - 6.0	Top	Perpendicular on the profile	100/500
KC89 *	3.0 - 6.0	Side	Perpendicular on the profile	100/500
KC90 *	3.0 - 6.0	Side	Parallel direction of the profile	100/500

* = Also available with cable tie: 200 x 4.8 mm

** = Supplied with integrated cable tie: 160 x 3.6 mm

