

Plastic cable ties - Push mount



Technical specifications

Brand	: WKK
Material	: Polyamide 6.6
Operating temperature (°C)	: -40 °C up to +85 °C
Flammability class	: UL 94 V-2
Halogen-free	: Yes
Silicone-free	: Yes
Available colors	: Natural= ○ Black (UV resistant)= ●

Scan this QR code for article numbers, current prices and stock information and to order directly.

Type no.	Length (mm)	Width (mm)	Max. bundle diameter (mm)	Tensile strength (kg)	Hole diameter (mm)	Panel thickness (mm)	Type	PU (pcs.)	PU (pcs.)	
									PU 100 pcs.	PU 1.000 pcs.
PUSH MOUNT 110x2.5mm	110	2.5	22	8.1	Ø 4.8	~ 2.4	1	100/1.000	22.000	28.000
PUSH MOUNT 130x3.2mm	130	3.2	28	13.6	Ø 4.0	~ 2.0	1	1.000	-	24.000
PUSH MOUNT 130x4.8mm	130	4.8	25	22.2	Ø 6.4	~ 3.2	1	100	10.000	-
PUSH MOUNT 170x4.8mm	170	4.8	38	22.2	Ø 6.4	~ 3.2	1	100/1.000	8.000	8.000
PUSH MOUNT 190x4.8mm	190	4.8	45	22.2	Ø 6.4	~ 3.2	1	1.000	-	8.000
PUSH MOUNT 150x3.6mm	150	3.6	32	13.6	Ø 5.2	~ 2.8	2	100/1.000	22.000	22.000
PUSH MOUNT 200x4.8mm	200	4.8	46	22.2	Ø 6.3	~ 3.6	2	1.000	-	12.000

