

Plastic cable glands & accessories - Metric

Plastic Ex-cable glands - Metric - IP66



Technical specifications

Brand	: Jacob
Material	: Polyamide PA6
Connecting thread	: Metric (EN 60423)
Group (zone)	: II 2G (1, 2), II 2D (21, 22)
Marking	: Ex e IIC Gb, Ex tb IIIC Db
Temperature range	: -20 °C up to +70 °C (M12, M16, M20, M25, M32) : -55 °C up to +70 °C (M40, M50, M63)
Protection grade	: IP66
Test standard	: EN 60079-0:2012, IEC 60079-0:2011 : EN 60079-7:2007, IEC 60079-7:2006 : EN 60079-31:2009, IEC 60079-31:2008
EC-type certificate	: PTB 99 ATEX 3101 X (M12 x 1.5 - M16 x 1.5) : PTB 99 ATEX 3128 X (M20 x 1.5 - M63 x 1.5) : PTB 14 ATEX 1015 X
IECEx certificate	: IECEx PTB 05.0004X, IECEx PTB 14.0027X
Available colors	: Black (RAL 9005)= ● Blue (RAL 5015)= ●

For other Ex-products, see pages 111, 112, 117 & 118

Scan this QR code for article numbers, current prices and stock information and to order directly.

Art. no.	Connecting thread	Cable diameter (mm)	Thread length (mm)	PU (pcs.)
GHG9601955R0101	M12 x 1.5	5.0 - 7.0	8	20
GHG9601955R0121	M12 x 1.5	5.0 - 7.0	12	20
GHG9601955R0102	M16 x 1.5	7.0 - 10.0	8	20
GHG9601955R0122	M16 x 1.5	7.0 - 10.0	12	20
GHG9601955R0103	M20 x 1.5	9.5 - 13.0	8	20
GHG9601955R0123	M20 x 1.5	9.5 - 13.0	13	20
GHG9601955R0104	M25 x 1.5	13.5 - 17.5	8	20
GHG9601955R0124	M25 x 1.5	13.5 - 17.5	13	20
GHG9601955R01zz	M32 x 1.5	17.5 - 21.0	10	20
GHG9601955R01zz	M32 x 1.5	17.5 - 21.0	15	20
GHG9601955R0106	M40 x 1.5	22.0 - 28.0	10	10
GHG9601955R0126	M40 x 1.5	22.0 - 28.0	15	10
GHG9601955R0107	M50 x 1.5	28.0 - 35.0	12	10
GHG9601955R0127	M50 x 1.5	28.0 - 35.0	16	10
GHG9601955R0108	M63 x 1.5	36.0 - 48.0	12	5
GHG9601955R0128	M63 x 1.5	36.0 - 48.0	16	5