

Assortment heat shrink tubing in display

WKK offers a practical metal display which contains a wide range of thin-wall heat shrink tubing. The heat shrink tubing has a standard length of 1220 mm, is packed per type / size in a display box and can easily be taken out to be sold per piece or in small quantities. All bars will be delivered in black. Other colors can be delivered on request.



Specifications types of heat shrink tubing

H-2(Z):

Thin-wall heat shrink tubing / flexible / 2:1

Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1
- Flame retardant and self-extinguishing
- General purpose
- High flexibility

Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black
- Other colors are available on request: red, blue, yellow, green, white
- In lengths of 1220 mm

H-5(3X)-F:

Thin-wall heat shrink tubing / flexible / 3:1 / adhesive lined

Features:

- Crosslinked co-extruded adhesive lined Polyolefin
- Shrink ratio: 3:1
- Flame retardant and self-extinguishing
- Excellent sealing and insulation properties
- UV-resistant

Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +110 °C
- Longitudinal change: 0 ± 10% max.

Order information:

- Color: black
- In lengths of 1220 mm

Content display

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Number of pieces in display
H-2(Z) 2:1 2,4/1,2	2,4	1,2	0,44	50
H-2(Z) 2:1 3,2/1,6	3,2	1,6	0,44	50
H-2(Z) 2:1 4,8/2,4	4,8	2,4	0,51	25
H-2(Z) 2:1 6,4/3,2	6,4	3,2	0,56	25
H-2(Z) 2:1 9,5/4,8	9,5	4,8	0,56	10
H-2(Z) 2:1 12,7/6,4	12,7	6,4	0,65	10
H-5(3X)-F 3:1 3,0/1,0	3,0	1,0	1,00	50
H-5(3X)-F 3:1 4,8/1,5	4,8	1,5	1,00	25
H-5(3X)-F 3:1 6,0/2,0	6,0	2,0	1,00	25
H-5(3X)-F 3:1 9,0/3,0	9,0	3,0	1,40	10
H-5(3X)-F 3:1 12,0/4,0	12,0	4,0	1,60	10
H-5(3X)-F 3:1 19,0/6,0	19,0	6,0	2,15	5